

## CLAIMS

In view of the foregoing, what is claimed is:

1. A computing system, comprising:  
a plurality of pipelined processors, each processor having a power dissipation  
5 controller for variably controlling internally generated power  
dissipation to a capacitive model which achieves substantially  
maximum average power output dissipation relative to throttled  
instruction input rate; and  
a cooler for cooling the system relative to power dissipated from the  
10 processors.
2. A system of claim 1, further comprising operating system software for  
specifying constants within register memory within the controller, the constants  
forming the capacitive model.
3. A system of claim 1, wherein the controller inserts a lp-bit to one or  
15 more stage execution circuits within the processor in order to stall high powered  
instructions through a pipeline.
4. A system of claim 1, wherein each processor further comprises at least  
one additional power dissipation controller for controlling processing in different  
pipelines.
- 20 5. A pipelined processor of the type having at least one register pipeline,  
comprising:  
a power dissipation controller for stalling instructions to control average power  
dissipation of the pipelined processor; and  
logic for comparing a threshold to current capacity of the pipelined processor  
25 and for implementing a low power state within the register pipeline of  
the pipelined processor when the capacity exceeds the threshold.
6. The pipelined processor of claim 5, further comprising register  
memory for storing constants of capacitive feedback.

7. The pipelined processor of claim 6, the constants being written to the register memory and including a bleed rate, one or more issue weights, and the threshold.

5 8. The pipelined processor of claim 7, the logic computing current capacity as a number of issued instructions multiplied by the issue weights and subtracted by the bleed rate.

9. The pipelined processor of claim 8, the issue weights corresponding to relative power dissipation, wherein issue weights for higher power instructions are greater than issue weights for lower power instructions.

10 10. The pipelined processor of claim 5, the power dissipation controller inserting a low power operation to the register pipeline to stall the instructions.

11. A power dissipation controller for controlling power dissipation within a pipelined processor, comprising:

a register access bus for setting a bleed rate;  
15 logic for multiplying each instruction of the pipelined processor by an issue weight; and  
logic for stalling instructions of the pipelined processor when capacity of the pipelined processor exceeds a threshold, wherein the capacity is determined as being (a) reduced by the bleed rate and (b) increased by  
20 the instruction multiplied by the issue weight.